

The invention claimed is:

1. An isolator to be used in a suspension system for a vehicle, the isolator comprising:

a front shaft;

5 a rear shaft;

means for attaching said front shaft and said rear shaft to the vehicle, said front shaft and rear shaft being rotatable relative to said attaching means;

a front transitional arm attached to said front shaft;

a rear transitional arm attached to said rear shaft;

10 a resilient member attached to said front transitional arm and attached to said rear transitional arm;

a front link arm attached to said front shaft;

a rear link arm attached to said rear shaft;

15 wherein when force is applied to said front link arm, said front shaft and said front transitional arm rotate and said resilient member is compressed or expanded; and

wherein when force is applied to said rear link arm, said rear shaft and said rear transitional arm rotate and said resilient member is compressed or expanded.

2. An isolator as defined in claim 1, wherein

20 said front transitional arm is a slack adjuster and said rear transitional arm is a slack adjuster;

said front transitional arm being capable of rotation relative to said front shaft;

and

said rear transitional arm being capable of rotation relative to said rear shaft.

3. An isolator as defined in claim 2, further including:

25 a shaft aperture within said front transitional arm having a spline therein;

a shaft aperture within said rear transitional arm having a spline therein;

a spline on at least a portion of said front shaft;

a spline on at least a portion of said rear shaft;  
wherein said portion of said front shaft is positioned within said shaft aperture  
in said front transitional arm and said spline on said front shaft mates with said spline  
of said front transitional arm; and

5            wherein said portion of said rear shaft is positioned within said shaft aperture  
in said rear transitional arm and said spline on said rear shaft mates with said spline of  
said rear transitional arm.

4.        An isolator as defined in claim 2, further including:  
          a front transitional arm adjustment associated with said front transitional arm  
10        for rotating said front transitional arm relative to said front shaft; and  
          a rear transitional arm adjustment associated with said rear transitional arm for  
rotating said rear transitional arm relative to said rear shaft.

5.        An isolator as defined in claim 1, wherein said resilient member is an air bag.

6.        An isolator as defined in claim 5, wherein said front transitional arm further  
15        includes a front air bag attachment bracket and said rear transitional arm further  
includes a rear air bag attachment bracket and wherein an air bag aperture is provided  
through one of said air bag attachment brackets.

7.        An isolator as defined in claim 6, further including an air hose connected to  
said air bag aperture.

20        8.        An isolator as defined in claim 5, wherein said front transitional arm further  
includes at least one rearward extending safety stop and wherein said rear transitional  
arm further includes at least one forward extending safety stop.

9. An isolator as defined in claim 1, wherein said front transitional arm is fixedly attached to said front shaft and wherein said rear transitional arm is fixedly attached to said rear shaft.
10. An isolator as defined in claim 1, further including:  
5 a front shackle mounted to said front spring arm, and  
a rear shackle mounted to said rear spring arm.
11. An isolator as defined in claim 10, wherein said front shackle and said rear shackle can be exchanged for an alternative front shackle and rear shackle.
- 10 12. An isolator as defined in claim 1, wherein said attaching means includes:  
bearings mounted proximate ends of said front shaft; and  
bearings mounted proximate ends of said rear shaft.
13. An isolator as defined in claim 12, wherein said bearings are tapered.
14. An isolator as defined in claim 1, wherein said attaching means includes:  
15 an inner bearing plate mounted proximate inner ends of said front and rear shafts; and  
an outer bearing plate mounted proximate outer ends of said front and rear shafts.
- 20 15. A suspension system for a vehicle having a frame a front axle and a rear axle, the suspension system comprising:  
a front leaf spring having a first end and a second end, said first end being attached to the frame of the vehicle and supporting a front axle;  
a rear leaf spring having a first end and a second end, said first end being  
25 attached to the frame of the vehicle and supporting a rear axle;

- an isolator including:  
a front shaft;  
a rear shaft;  
means for attaching said front shaft and said rear shaft to the vehicle, said front  
5 shaft and rear shaft being rotatable relative to said attaching means;  
a front transitional arm attached to said front shaft;  
a rear transitional arm attached to said rear shaft;  
a resilient member attached said front transitional arm and attached to said rear  
transitional arm;  
10 a front link arm attached to said front shaft;  
a rear link arm attached to said rear shaft;  
a front shackle attached to said front link arm and to said front leaf spring;  
a rear shackle attached to said rear link arm and to said rear leaf spring;  
wherein when force is applied to said front leaf spring, said front link arm,  
15 said front shaft, and said front transitional arm rotate and said resilient member is  
compressed or expanded; and  
wherein when force is applied to said rear leaf spring, said rear leaf spring,  
said rear shaft, and said rear transitional arm rotate and said resilient member is  
compressed or expanded.
- 20 16. A suspension system as defined in claim 15, wherein  
said front transitional arm is a slack adjuster and said rear transitional arm is a  
slack adjuster;  
said front transitional arm being capable of rotation relative to said front shaft;  
and  
25 said rear transitional arm being capable of rotation relative to said rear shaft.
17. A suspension system as defined in claim 16, further including:  
a shaft aperture within said front transitional arm having a spline therein;

a shaft aperture within said rear transitional arm having a spline therein;  
a spline on at least a portion of said front shaft;  
a spline on at least a portion of said rear shaft;  
wherein said portion of said front shaft is positioned within said shaft aperture  
5 in said front transitional arm and said spline on said front shaft mates with said spline  
of said front transitional arm; and  
wherein said portion of said rear shaft is positioned within said shaft aperture  
in said rear transitional arm and said spline on said rear shaft mates with said spline of  
said rear transitional arm.

10 18. A suspension system as defined in claim 15, further including:  
a front transitional arm adjustment associated with said front transitional arm  
for rotating said front transitional arm relative to said front shaft;  
a rear transitional arm adjustment associated with said rear transitional arm for  
rotating said rear transitional arm relative to said rear shaft; and  
15 wherein upon rotation of said front transitional arm relative to said front shaft,  
said front leaf spring moves upward or downward and upon rotation of said rear  
transitional arm relative to said rear shaft, said rear leaf spring moves upward or  
downward.

20 19. A suspension system as defined in claim 15, wherein said front transitional  
arm is fixedly attached to said front shaft and wherein said rear transitional arm is  
fixedly attached to said rear shaft.

20. A suspension system as defined in claim 15, wherein said resilient member is  
an air bag.

25 21. A suspension system as defined in claim 20, further including a fill valve in  
fluid communication with said air bag.

22. A suspension system as defined in claim 20, further including an air pressure gauge in fluid communication with said air spring.

23. A method for adjusting the ride height of a vehicle having a frame comprising the steps of:

providing a suspension system including:

a front leaf spring having a first end and a second end, said first end being attached to the frame of the vehicle;

a rear leaf spring having a first end and a second end, said first end being attached to the frame of the vehicle;

an isolator including:

a front shaft,

a rear shaft,

a front transitional arm attached to said front shaft,

a rear transitional arm attached to said rear shaft,

a resilient member attached to said front transitional arm and attached to said rear transitional arm,

a front link arm attached to said front shaft,

a rear link arm attached to said rear shaft,

a front shackle attached to said front link arm and to said second end of said front leaf spring;

a rear shackle attached to said rear link arm and to said second end of said rear leaf spring;

lengthening or shortening the front spring shackle and the rear spring shackle to achieve the desired ride height.

24. A method for adjusting the ride height of a vehicle having a frame comprising the steps of:

providing a suspension system including:

a front leaf spring having a first end and a second end, said first end being attached to the frame of the vehicle;

a rear leaf spring having a first end and a second end, said first end being attached to the frame of the vehicle;

5 an isolator including:

a front shaft,

a rear shaft,

a front transitional arm attached to said front shaft,

a rear transitional arm attached to said rear shaft,

10 a resilient member attached to said front transitional arm and attached to said rear transitional arm,

a front link arm attached to said front shaft,

a rear link arm attached to said rear shaft,

15 a front shackle attached to said front link arm and to said second end of said front leaf spring;

a rear shackle attached to said rear link arm and to said second end of said rear leaf spring;

rotating said front transitional arm relative to said front shaft to raise or lower said front leaf spring; and

20 rotating said rear transitional arm relative to said rear shaft to raise or lower said rear leaf spring.